

OHAUS PX2201 Precision Balance/ InCal 2200 x 0.1 mg

ME482201

Description

The PX2201 offers high accuracy and repeatability for essential weighing applications in laboratory, industrial and education settings at an economical price point. Featuring a cast metal lower housing, sub-pan and stainless steel weighing pan, the PX is durably constructed for versatile, long-term use. The PX features a second line display for additional information or guidance, a static removal bar for convenient grounding, and USB and RS232 connectivity for easy communication.



Specifications

Capacity	2200 g
Readability	0.1 mg
Pan Size	Ø 180 mm
Display	2-Line LCD with Backlight
Operation	AC adaptor (included)
Communication	RS232 (included) and USB
Internal Calibration	InCal™ - Semi Automatic
Draftshield	N/A
Auto Door	N/A
Dimensions (H x L x W)	98 mm x 321 mm x 209 mm
In-Use Cover	N/A
Minimum Weight	82 mg
Net Weight	3.5 kg
Stabilisation Time	1 s
Tare Range	To capacity by subtraction
Units of Measurement	Carat; Custom; Grain; Gram; Hong Kong Tael; Kilogram; Mesghal; Milligram; Momme; Newton; Ounce; Ounce Troy; Pennyweight; Pound; Singapore Tael; Taiwan Tael; Tical; Tola
Working Environment	10°C – 30°C, 80%RH, non-condensing
Construction	Metal base, plastic top housing, removable stainless steel pan

Design Features

- Real Time Clock with GLP/GMP Data
- Integrated weigh-below-hook
- Security bracket
- Calibration lock and in-use cover
- User-selectable environmental filters and brightness settings
- Auto-tare
- Auto-dim
- User-selectable span calibration points
- Overload indicator
- Software lockout and reset menu
- User-selectable communication settings and data print options
- User-definable project and user IDs
- Software overload/underload indicator
- Stability indicator
- Four operating languages