

## OHAUS PX5202 Precision Balance/ InCal 5200 x 0.01 mg

ME485202

### Description

The PX5202 offers high accuracy and repeatability for essential weighing applications in laboratory, industrial and education settings at an economical price point. Featuring a cast metal lower housing, sub-pan and stainless steel weighing pan, the PX is durably constructed for versatile, long-term use. The PX features a second line display for additional information or guidance, a static removal bar for convenient grounding, and USB and RS232 connectivity for easy communication.



### Specifications

<b>Capacity</b>	5200 g
<b>Readability</b>	0.01 mg
<b>Pan Size</b>	Ø 180 mm
<b>Display</b>	2-Line LCD with Backlight
<b>Operation</b>	AC adaptor (included)
<b>Communication</b>	RS232 (included) and USB
<b>Internal Calibration</b>	InCal™ - Semi Automatic
<b>Draftshield</b>	N/A
<b>Auto Door</b>	N/A
<b>Dimensions (H x L x W)</b>	98 mm x 321 mm x 209 mm
<b>In-Use Cover</b>	N/A
<b>Minimum Weight</b>	82 mg
<b>Net Weight</b>	3.5 kg
<b>Stabilisation Time</b>	1 s
<b>Tare Range</b>	To capacity by subtraction
<b>Units of Measurement</b>	Carat; Custom; Grain; Gram; Hong Kong Tael; Kilogram; Mesghal; Milligram; Momme; Newton; Ounce; Ounce Troy; Pennyweight; Pound; Singapore Tael; Taiwan Tael; Tical; Tola
<b>Working Environment</b>	10°C – 30°C, 80%RH, non-condensing
<b>Construction</b>	Metal base, plastic top housing, removable stainless steel pan

### Design Features

- Real Time Clock with GLP/GMP Data
- Integrated weigh-below-hook
- Security bracket
- Calibration lock and in-use cover
- User-selectable environmental filters and brightness settings
- Auto-tare
- Auto-dim
- User-selectable span calibration points
- Overload indicator
- Software lockout and reset menu
- User-selectable communication settings and data print options
- User-definable project and user IDs
- Software overload/underload indicator
- Stability indicator
- Four operating languages